MTV-73SS10H COLOR CAMERA INSTRUCTION

Caution for Installation

- 1. Avoid places where there is direct sunlight. When using the camera outside.
- 2. Be careful, never let any water in this equipment.
- 3. Do not directly touch the CCD element. If necessary, use a soft cloth moistened with alcohol to wipe off the dust.
- 4. When the camera installs in dust or wet environment, please puts into the camera housing.
- 5. Be extra careful not to shake the camera.
- 6. Avoid places where temperatures exceed 50°C or more.
- 7. When any abnormalities occur, make sure to unplug the unit and contact your local dealer.
- 8. The camera are only operated with regulative adaptor DC 12V,


AC to DC non-regulative adaptor may cause camera damaged.

SPECIFICATION (RoHS Conform)


MODE NO.		MTV-73SS10HN	MTV-73SS10HP	
TV SYSTEM		NTSC	PAL	
IMAGE SENSOR		1/3-inch I.L. CCD Image Sensor		
CCD TOTAL PIXELS		~ 410K	~ 470K	
SYNC SYSTEM		Internal		
MINIMUM ILLUMINATION		0.012 Lux F1.2 / 40 IRE AGC on 0.0014Lux F1.2 / 40 IRE SENS-UP (32X)		
LENS & VIEW ANGLE				
RESOLUTION		540 TVL		
WHITE BALANCE	Mode	ATW / AWC		
	Range	3200 ∼ 10000 °K		
S/N RATIO		50dB (MIN) / 58dB (TYP) (0	50dB (MIN) / 58dB (TYP) (Gamma, Aperture, AGC, OFF)	
DNR (Digital Noise Reduce)		S/N UP 4.5dB		
GAIN CONTROL		AGC ON / OFF		
SENSE UP		ON /OFF (Preset X4 ,Option X32)		
H - MIRROR FUNCTION		OFF / ON		
V - MIRROR FUNCTION		OFF / ON		
B.L.C. FUNCTION		ON / OFF		
COLOR BAR		OFF / ON		
AUTO IRIS		A.E.S. / DC-IRIS		
ELECTRONIC SHUTTER		1/60~1/120,000 sec.	1/50~1/120,000 sec.	
VIDEO OUTPUT		1.0V p-p composite video at 75 ohm With monitor output		
OPERATION TEMPERATURE		-20°C TO 50°C		
OPERATIONAL HUMIDITY		within 85% RH		
POWER SUPPLY		DC12V±1V / 150mA		

^{*}The specifications and appearance of the product may changed without notice.

Dimension: Unit (mm / ±0.5mm)



Auto IRIS Lens Connector:



DC-LENS				
P1	DUMP-			
P2	DUMP+			
P3	DRIVE			
P4	GND			

Function Switch

FUNCTION SWITCH		1	0				
S1	AES/ALC	AES	ALC				
S2	AGC	AGC ON	AGC OFF				
S3	ATW/AWC	ATW	AWC				
S4	BLC	BLC ON	BLC OFF				
S5	H-MIRROR	NORMAL	MIRROR				
S6	V-MIRROR	NORMAL	MIRROR				
S7	SENS-UP (X4)	SENS-UP ON	SENS-UP OFF				
S8	VIDEO/COLOR BAR	VIDEO	COLOR BAR				